

TECHNICAL DATA SHEET (TDS)

LIQUID PREPARATION WAX

ID Product Code 002

Pag | 1

Liquid wax for polishing corner and edges of marble, terrazzo, engineered stone, granite, stone and cement.



Product description:

Liquid product to polish any type of stone. It can be use by hand or in automatic. Its fast dry time allows to make following operations very quickly. Polisher for corners and edges of marble, granite, travertine, tiles and agglomerate stones. It enhances color. Thanks to its easy application can be used for cladding wall and on not flat surfaces as statues or vases. Typical use of LIQUID PREPARATION is on floors to enhance color and shine to the corners after grinding. It is also appropriate for treatment of edges, bull noose etc... LIQUID PREPARATION can be applied on any type of stone grinded over grid 800 in order to enhance color and shine. Its particular formula gives waterproof properties to the stone.

Chemical characteristics:

| Appearance | Liquid | |
|-----------------------------------|---------------------------------|--|
| Color | Clear transparent | |
| Odor | Characteristic of solvent | |
| Specific gravity at 20° C (68° F) | 1,48±0,02 | |
| Hydro-solubility | Not soluble | |
| рН | N.A. | |
| Shelf life at 20°C (68° F) | 24 months in original container | |

^{*} indicative values, depending on the nature of the material and environmental conditions

Instruction for use

Apply evenly the product on the surface to treat (surface has to be clean and without powder). Let it dry for 5-10 minutes (in dependence of temperature). To reach a very brilliant result is necessary to buff with dry soft cloth, with fine steel wool (00 or 000) or by brush. It is also possible to polish the stone using an electrical flex machine (max. 2000 rpm) equipped with felt disc or cloth disc.

If the product is applied on the floor, it can be polished using a buffing machine with steel wool or floor polish machine equipped with steel wool disc or polishing disc supplied with the machine.

Suggestion for use and recommendations:

- It is not advised to apply the product on synthetic materials as plastics, linoleum and laminate.
- Apply on clean and dry surfaces.
- Perform a preliminary test on a small area before actual use.
- Read carefully recommendations printed on the label and perform always a preliminary test before use.

Application surfaces

Marble, granite, terrazzo, agglomerated and stones.





All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure. Bellinzoni srl reserves the right to make changes to the products shown in this card, at any time without prior notice. The pictures shown are approximate, as a printed reproduction causes inevitable differences.







TECHNICAL DATA SHEET (TDS)

Application tools







Pag | 2

Cloth Angle grinder Single Disc

Coverage

For polishing of marble and granite polished or grinded above grit 800, with 750 ml (25 fl. oz.) of product is possible to treat 20/30 sqm (200/300 sq.ft.) In case of calcareous stone, limestone, sand stone, concrete polished or grinded above grit 800 with 1 kg (35 oz.) of product, it is possible to treat 15/25 sqm (160/240 sq.ft.).

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com

Packing

| Item N° | Packing | Pcs |
|-----------|----------------------|-----|
| 002APL01 | 750 ml (25 fl. oz.) | 12 |
| 002APL05 | 5,00 kg (11 lbs.) | 3 |
| 002APL30 | 30,00 kg (66 lbs.) | 1 |
| 002APL200 | 200,00 kg (440 lbs.) | 1 |

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

H.S. Code

34.04.9000

Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product LIQUID PREPARATION WAX is MADE IN ITALY.





All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure. Bellinzoni srl reserves the right to make changes to the products shown in this card, at any time without prior notice. The pictures shown are approximate, as a printed reproduction causes inevitable differences.



