

ANTIK

PRODUCT DESCRIPTION

Solvent based, “antique effect” enhancer and water repellent, indicated for all textured marbles, granites and natural stones. Highly recommended on sand blasted, tumbled, bush hammered or flamed stone surfaces. Product protects surfaces from general staining from oils, water and grease build ups, while reducing staining caused by moisture and humidity. Product supplies an “durable gloss” finish, enhancing the beauty and natural features of the stone. Internal tests show that product offers a high resistance to UV rays and reduces the formation of mold and mildew over time.

APPLICATION SURFACES

Indicated for textured marbles, travertine, stone, granite and porous materials

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Liquid
COLOR:	Transparent
ODOR:	Characteristic
SPECIFIC GRAVITY AT 20°C:	0,96 +/- 0,05 g/cm3
SOLUBILITY:	Insoluble
PH:	N.A.
STORAGE AT 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application.

Ensure that surfaces to be treated are completely dry and clean, free of dirt, dust, grime and surface incrustations.

Cover and protect all surrounding areas before proceeding with application.

Manual: product is ready for use. Apply a coat of product uniformly using a soft bristled brush, microfiber cloth, wax applicator or a roller to material. Allow surface to absorb product completely.

After 10-15 minutes, remove all eventual excess product, pooling or residues using a clean cotton cloth or microfiber, until all excess product is absorbed.

On highly porous materials, sandblasted materials, flamed and bush-hammered, we suggest applying a second coat of product within 1-2 hours from the first.

Notes: During application, product should be applied to materials with temperature between 10° and 30°C. Before application to floors with underfloor heating, turn off all heating and allow floor to cool completely before product application. Maintain product in its original container/packaging. Always test product first.

RECOMMENDATIONS

Do not dilute with water or solvents. Excess product or supplication will cause a glossy effect. On highly absorbent materials apply two coats of product “wet on wet” We recommended to apply product until complete surface saturation. Treatment will not protect surface from etching caused by acidic substances or general surface wear. Protect treated surfaces from rain, humidity or moisture for 12 hours following application. Allow treated surfaces to dry completely for 48 hours before use. Complete protection will become effective after 7 days from application.

Before use, read completely product label, technical data sheet and safety data sheet.

INDICATED COVERAGE

For protection of marble and granite polished or grinded after grid 800, with 1 liter (1 quart) of product is possible to treat 30/40 sqm (320/430 sq.ft.) In case of calcareous stone, limestone, sand stone, concrete, with 1 liter of product it is possible to treat 10/15 sqm (100/160 sq.ft.)*

(*) depending on the number of coats, texture and porosity of the surface.

PACKAGING

CODE	CONTENT	PCS PER BOX
065CANT001	1lt	6

For further information: www.bellinzoni.com

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.