

GREZZO

PRODUCT DESCRIPTION

Silicone based, colour enhancer and protective to increase colour and aspect, increasing surface resistance to water and oils on various textured materials; marbles, granites, natural stone and agglomerates. Treated material maintain a uniform intense “wet look” effect. Breathable and deep penetrating solution, product does not leave surface residues, films or plastic effects.

APPLICATION SURFACES

Indicated for marbles, granites, flamed, honed, antique and split-face materials

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Liquid
COLOR:	Transparent yellow
ODOR:	Characteristic
SPECIFIC GRAVITY AT 20°C:	0,86 +/- 0,05 g/cm ³
SOLUBILITY:	Insoluble
PH:	N.A.
STORAGE AT 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application. Ensure that surfaces to be treated are completely dry and clean, free of dirt, dust, grime and surface incrustations. Cover and protect all surrounding areas before proceeding with application.

Manual: Product is ready for use. Apply a coat of product uniformly using a soft bristled brush, microfiber cloth, wax applicator or a roller to material. Allow surface to absorb product completely.

After 30 minutes, remove all eventual excess product, pooling or residues using a clean cotton cloth or a dampened cloth with turpentine until all excess product is absorbed.

On highly porous materials, apply a second coat of product within 1-2 hours from the first.

Notes: During application, product should be applied to materials with temperature between 10° and 30°C. Before application to floors with underfloor heating, turn off all heating and allow floor to cool completely before product application. Maintain product in its original container/packaging. Always test product first.

RECOMMENDATIONS

Do not dilute with water or solvents. On highly absorbent materials apply two coats of product “wet on wet” We recommended to apply product until complete surface saturation. Treatment will not protect surface from etching caused by acidic substances or general surface wear. Protect treated surfaces from rain, humidity or moisture for 12 hours following application.

Allow treated surfaces to dry completely for 48 hours before use. Complete protection will become effective after 7 days from application. Before use, read completely product label, technical data sheet and safety data sheet.

INDICATED COVERAGE

Textured natural stone surfaces: 10 m² *

(*) depending on the number of coats, texture and porosity of the surface.

PACKAGING

CODE	CONTENT	PCS CARTON
068CGREZZO001	1 lt	6
068CGREZZO005	5 lt	2
068CGREZZO005	25 lt	1

For further information: www.bellinzoni.com

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.