

SILICONE BASED, LIQUID WAX FOR MANUAL OR AUTOMATIC POLISHING OF MARBLE, GRANITE, CERAMIC, TERRAZZO, NATURAL STONE AND GRES.

VX SL

PRODUCT DESCRIPTION

Liquid polishing wax indicated for all materials. Ideal for manual application, but also indicated for automatic inline waxing machines. Due to its specific formulation, product increases surface gloss and shine, while leaving a breathable water repellent surface. With fast-drying properties, product allows a quick application and drying process. Highly recommended for automatic polishing machines for slabs and large formats or for polishing manually vertical surfaces and non-flat areas such as statues or vases. Can be used on all surfaces after an 800 grit to enhance colour and gloss.

APPLICATION SURFACES

Marble, granite, terrazzo, agglomerates, quartz and engineered stones.

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Liquid
COLOR:	Cloudy
ODOR:	Characteristic
SPECIFIC GRAVITY AT 20°C:	1,48 +/- 0,05 g/cm ³
SOLUBILITY:	Insoluble
PH:	N.A.
STORAGE AT 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application.

Ensure that surfaces to be treated are completely dry and clean, free of dirt, dust, grime and surface incrustations.

Cover and protect all surrounding areas before proceeding with application

Manual: using a clean cloth, spread VX-SL evenly over the surface. Allow product to dry for 5-10 minutes before buffing surface (depending on room temperature). Buff surface using a clean cotton cloth or fine steel wool pad. For quicker procedures, product can be buffed using a hand-held, rotary polisher (variable speed max. 2000 rpm) with a felt pad or cloth headset.

Floors: Using a clean cloth, spread VX-SL evenly over the surface. Allow product to dry for 5-10 minutes (depending on room temperature). Buff surface using a floor polishing machine or mono brush equipped with a white felt pad.

Automatic (inline): for automatic applications, product can be applied in waxing machines equipped with 1 electric fan to dry the material before waxing, 1 automatic timer-dispenser for the regulation of product quantity and timing of application, 1 distribution head for even distribution, 1 electric fan for drying the coated wax, 1 or 2 polishing heads with brushes.

Notes: During application, product should be applied to materials with temperature between 10° and 30°C. Before application to floors with underfloor heating, turn off all heating and allow floor to cool completely before product application. Maintain product in its original container/packaging. Always test product first. in its original container/packaging. Always test product first.

RECOMMENDATIONS

To increase product penetration, heat the slab or surface before applying the product. This will allow deeper penetration increasing final gloss. To slow down the drying process, product can be diluted with mineral solvent up to 30%. Product may cause floors to become slippery. Do not apply to syntactic materials such as plastics, linoleum and laminates. Surface must be completely dry before application. For internal use only. Before use, read completely product label, technical data sheet and safety data sheet.

INDICATED COVERAGE

To polish marbles and granites above 800 grit, indicated coverage is : 25/30 m²*

(*) depending on the number of coats, texture and porosity of the surface.

PACKAGING

CODE	CONTENT	PCS CARTON
004AVX01	1 kg	6
004AVX05	5 kg	4
004AVX30	30 kg	1
004AVX200	200 kg	1

For further information: www.bellinzoni.com

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.

Disclaimer: the present information supersedes and replaces all previous versions. All data indicated in this document are the results of tests and experiments carried out in our laboratories and through reliable operators within the stone business and have to be considered reliable. However, because of the many external and surrounding factors which can influence the final results, the information here reported does not constitute an implicit or a formal guarantee. The end user will undertake the full responsibility in the usage of the product, making sure to test first the product and to experiment with the product as a preventive measure so to understand its full and final characteristics. Bellinzoni has the right to modify any information mentioned on this document, at any time and without notice. Bellinzoni is the sole owner of all trademarks and logos indicated in this document and to copy or modify in part or in full, without permission can infringe property rights. Bellinzoni will not be held responsible for its incorrect use and will follow legal proceedings as of current law.