

PRODUCT DESCRIPTION

Polishing powder specific for the polishing and gloss maintenance of marble, travertine, agglomerates, terrazzo and limestone surfaces to obtain a high gloss finish. With every use, product hardens and protects surfaces from scratches and scuffs, while giving a high natural look gloss. Ideal for use in high traffic or commercial areas where general foot traffic will lower gloss and shine over time.

APPLICATION SURFACES

Polished marbles, marble agglomerates and natural stones.

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Powder
COLOR:	Yellow
ODOR:	Odourless
SPECIFIC GRAVITY AT 20°C:	1,00 +/- 0,05 g/cm ³
SOLUBILITY:	Partially Soluble
PH:	N.A.
STORAGE AT 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application. Ensure that surfaces to be treated are completely dry and clean, free of dirt, dust, grime and surface incrustations. Cover and protect all surrounding areas before proceeding with application. Remove any previous surface waxes or coatings (see our ULTRA STRIPPER) before proceeding with application

Floors:

1. Apply SUPER CRYSTAL directly to the floor manually over the area to be treated, sufficient for approximately a couple of square metres (approx. 20 square feet) per application. Position the single disc machine equipped with a natural white pad on the floor.
2. Proceed to spray water onto the powder or through the machines tank and work the powder until a creamy mix has formed. Add water or product to maintain a creamy mixture.
3. Work small areas at a time (1-2m²). DO NOT ALLOW MIXTURE TO DRY ON SURFACE. ADD WATER IF NECESSARY.
4. Continue to polish until desired gloss is obtained. Check surface using a window squeegee to remove sludge.
5. Remove sludge from surface or repeat process adding more powder and water and move onto next area and proceed as indicated.
6. Wet vacuum all residues and rinse area using clean water and solution of HYDRO STONE SOAP.

Notes: Excessive product may burn surface. Do not work on the same areas for long periods of time. We highly recommend the use of our PHOENIX EH (30-45kg) with natural fibre pad for the application of product. Work small areas at a time (1-2m²). Before use, read completely product label, technical data sheet and safety data sheet.

INDICATED COVERAGE

With 1 kg of product: 40/50 m²*

(*) depending on the number of coats, texture and porosity of the surface.

PACKAGING

CODE	CONTENT	PCS CARTON
074PCRYSTALUX01	1 kg	6
074CRYSTALUX05	5 kg	4
074CRYSTALUX25	25 kg	1

For further information: www.bellinzoni.com

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.