# **B-BLOCK NAT CK**



#### **ANTI STAIN NATURAL LOOK**

Water based, odourless, water/oil repellent impregnating sealer it maintains the natural finish to the material. Great "bead effect" it prevents water from pooling, protecting the surface from moisture and stains in general. It prevents dirt and grime to stick and penetrate to the surface pores therefore

making it easier to remove the dirt with a neutral, solvent free detergent

(B-LEM 3 EXXTRA CK)



B Bellinzoni

Brat ANTIMACCHIA

IDRO-OLEO REPELLENTE

#### **CHEMICAL PROPERTIES**

APPEARANCE: Liquid

COLOUR: Colourless

ODOUR: Odourless

SOLUBILITY: Soluble in water

PH: 4,50±0,50

#### **COVERAGE FOR LITRE**

Unglazed terracotta: Approximately 8-12 m<sup>2</sup>

Clinker: 10-14 m<sup>2</sup>

(Product coverage may vary depending on type and porosity of material where used)

PACKING Code	Content	Pc./Carton
P092BLCK10L	1 lt	6
P092BLCK50L	5 lt	4

www.bellinzoni.com

MADE IN ITALY • 0 •

## **SURFACES**

The product is recommended for terracotta, quarry tiles and klinker.

## **FEATURES**

Protective water-based solution for all indoor and outdoor hard surfaces, it can be used on damp surfaces.

### METHOD OF USE

Remove from the surface all debris, dust and previous applied waxes using XTREME HD CLEANER or SUPER CLEANER. The surfaces must be dust free, clean and dry before application. The product is ready to use. Apply a thin coat of product uniformly in one direction using a brush, microfiber cloth, wax applicator or roller. Let it dry for approximately 15-20 minutes before applying a second coat in the opposite direction from the first. Remove the excess product or residues, if any, within 15 minutes from application with a dry cotton or microfiber cloth.

## **ADVANTAGES**

It protects the surfaces from a wide range of oil and water based staining substances. Durable, UV resistant and non-yellowing protector, the product let the material "breath". Due to its hydrophobicity the product prevents liquids and moisture absorption, preventing the growth of mildew and mould. The treated surfaces are maintained quicker and easier due to its "easy-clean" effect. Due to its zero VOC content the product can be safely used indoors or little ventilates places. Thanks to its specific formulation, the product respects the requirements of 2010/2015 PFOA Stewardship Program US FPA (related to the Impact on human health and environment).

## **ADVICE**

Do not walk on the treated surfaces for at least 6-8 hours from application. The surfaces are full protected after 24 hours from application.



formation:

#### ATTENTION:

Carefully read the recommendations printed on the label. Store in the original packaging. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. The product can revive some materials, check in advance on a small portion of the surface. It does not protect against the action of acids. When using the product, use suitable PPE and consult the safety data sheet.