B-WAX GLOSSY MG



SELF POLISHING WAX FOR FLOORS

Single application, self-polishing, high coverage polisher for high traffic surfaces.



CHEMICAL PROPERTIES

APPEARANCE: Liquid
COLOUR: White
ODOUR: Lavender
SOLUBILITY: Miscible in water
PH: 9,00 ± 0,50

COVERAGE FOR LITRE

Polished marble and natural stone floors: Approximately 30 m₂ - one coat. (Product coverage may vary depending on type and porosity of material where used)

PACKAGING	Content	Pc./Carton
P116WGMG10L	1 lt	6
P116WGMG50L	5 lt	4
£		
for information:	www.bellinzoni.com	

MADE IN ITALY

ATTENTION:

SURFACES

Product is recommended for all hard floor surfaces i.e.: marble, granite and natural stone surfaces.

FEATURES

High gloss, single application metallic floor polisher with excellent resistance to wear-and-tear, frequently washed and high traffic floors. The product restores the original lustre and shine to all dull and worn-out surfaces, leaving a protective layer on material. Due to its self-polishing characteristics, the product does not require any further application and on-going maintenance once applied. The product is well spreadable even at low temperatures due to its formulation containing softeners and plasticizers. Effective in correcting minor surface defects, micro scratches and dullness. The product leaves a long-lasting flowery fragrance after its use. Easy surface maintenance due to its "easy clean" effect.

HOW TO USE

Remove debris, dust and previous applied waxes from the surface using XTREME HD CLEANER or SUPER CLEANER. Manual application: apply the product evenly over clean and dry surface using specific microfiber, wax applicator or clean cloth. The application must be on one direction without overlapping or criss-crossing. Wait for at least 60 minutes drying time before walking over the treated floor.

ADVANTAGES

Fast drying and hardening, high gloss and excellent resistance to high traffic. Long lasting fragrance. Ultra-durable, contains dissolved polymers and polyurethane for extra surface durability. One coat is sufficient.

ADVICE

Remove all existing and previous applied waxes before application. Avoid the formation of foam or bubbles during application. Avoid dust to settle on the wet floor and do not walk on the treated surfaces until completely dry. It should not be used on damp, humid places or in constantly wet areas such as showers and bathrooms. For ongoing surface maintenance, use LEM 3 EXXTRA MG as indicated.

Carefully read the recommendations printed on the label. Always test before use. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. The product has anti-stain properties but does not protect surfaces from acids. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. When using the product, use suitable PPE and consult the safety data sheet.