# **B-WATER BLOCK**



#### PROTECTIVE, WATER REPELLENT

Water based, protective water repellent for the protection of natural stone and masonry surfaces.



#### CHEMICAL PROPERTIES

APPEARANCE: Liquid			
COLOUR: White			
ODOUR: Odourless			
SOLUBILITY: Soluble in water			
PH: 5,50 ± 0,50			

#### **COVERAGE FOR LITRE**

Polished marble: Approximately 20-30 m<sup>2</sup> Terracotta, brick and masonry surfaces: Approx. 8-15 m<sup>2</sup>

(Product coverage may vary depending on type and porosity of material where use	ed

PACKAGING		
Code	Content	Pc./Carton
P121WBK10L	1 lt	6
P121WBK50L	5 lt	4
for information:	www.bellinzoni.com	

SURFACES

The product is recommended for marbles, natural stones, granites, terracotta, architectural bricks and concrete.

## FEATURES

Innovative, water repellent, bead effect gives long lasting protection to all external masonry surfaces. It does not change the natural aspect of material and penetrates deeply. The "3-size" nano-molecules are small enough to penetrate even the smallest pores of most substrates, keeping external water from entering the substrate. Treated surfaces remain breathable. The product is UV resistant and non-yellowing. The protected surfaces are maintained with ease due to its "easy-clean" effect. Its neutral pH formulation allows the product to be used also around metals. Due to its water hydrophobic property, it prevents the growth of mildew and mould. It protects against weathering, efflorescence and freeze-thaw damage.

### **HOW TO USE**

The surface to be treated must be clean and dry. Remove all dirt, mould and grime from the surface before application. The product is ready for use. Apply to the surface evenly with a large bristled brush, roller or low-pressure spraygun until saturation. Leave it on for 45 minutes then remove the excess, if any, using a clean cloth.

## ADVANTAGES

Durable long-lasting protection. UV resistant and non-yellowing. It lets the material breath by allowing vapours to escape. For indoor and outdoor use. The product has no VOC content.

## ADVICE

Let the product dry completely for 6-8 hours from application before walking over the treated area. Full protection is achieved after 24 hours from application.



#### ATTENTION:

Carefully read the recommendations printed on the label. Always test before use. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. The product has anti-stain properties but does not protect surfaces from acids. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. When using the product, use suitable PPE and consult the safety data sheet.