

STRIP VAPOR

PRODUCT DESCRIPTION

Protective, anti-graffiti treatment ideal for the protection of external cladding and facades in natural stone, marble, granite statues and surfaces from graffiti, spray paints and felt pens. STRIP VAPOR thanks to its special water based microcrystalline based formulation, protects the surface creating a micro invisible barrier (allowing material to breath) avoiding eventual paint build ups penetrating in material. STRIP VAPOR is a sacrificial treatment and will need to be reapplied every time graffiti is removed from surface, either by high pressured water or by a mechanical action.

APPLICATION SURFACES

Indicated for all external polished stone and masonry surfaces

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Liquid
COLOR:	White
ODOR:	Odourless
SPECIFIC GRAVITY AT 20°C:	1,00+/- 0,05 g/cm ³
SOLUBILITY:	Soluble in all parts
PH:	9,00 ± 0,05
STORAGE AT 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application. Ensure that surfaces to be treated are completely dry and clean, free of dirt, dust, grime and surface incrustations. Cover and protect all surrounding areas before proceeding with application.

Spray: Product is ready for use. Spray surface lightly from top to bottom using a hand-held low-pressure pump. Avoid excessive products so to avoid run downs. Two coats are recommended. Let treatment dwell on surface for a few minutes before removing excess product. Treatment will be effective after 12 from application.

Graffiti Removal:

Graffiti can be removed using hot boiling water, which will breakdown the treatment and therefore remove all graffiti. In alternative, a mechanical cleaning can be carried out using a water pressure combination and nylon pads. For more stubborn graffiti, the product WALL CLEAN can be applied beforehand to dissolve stubborn build ups.

Notes: During application, product should be applied to materials with temperature between 10° and 30°C. Before application to floors with underfloor heating, turn off all heating and allow floor to cool completely before product application. Maintain product in its original container/packaging. Always test product first.

RECOMMENDATIONS

Multiple applications may be needed on porous stone surfaces Do not dilute. Excess product or application will cause a glossy effect. Treatment will not protect surface from etching caused by acidic substances or general surface wear. Protect treated surfaces from rain, humidity or moisture for 12 hours following application. Before use, read completely product label, technical data sheet and safety data sheet.

INDICATED COVERAGE

For protection of marble and granite polished or grinded after grid 800, with 1 liter (1 quart) of product is possible to treat 10/15 sqm (110/160 sq.ft.) In case of calcareous stone, limestone, sand stone, concrete polished or grinded after grid 800 with 1 litre of product, it is possible to treat 5/10 sqm (50/110 sq.ft.)

(*) depending on the number of coats, texture and porosity of the surface

PACKAGING

CODICE	CONTENUTO	PZ CARTONE
031CBEL01	1lt	6
031CBEL05	5 lt	4
031CBEL25	25 lt	1

For further information: www.bellinzoni.com

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.