

EPOBEL

PRODUCT DESCRIPTION

EPO BEL is a ready-to-use, concentrated pigment paste available in various colours, specifically designed for epoxy-based adhesives such as EPOX PREMIUM and EPOX 2000. Thanks to its high-quality pigments, EPO BEL blends easily with adhesives, allowing you to achieve the desired shade and to match the colours of different types of stone and surfaces. It is light-resistant, ensuring the colour remains stable even after the adhesive has been catalysed.

PRODUCT ADVANTAGES

- High colouring characteristics
- Colour does not shade
- Easy use and mixture
- Available in different colours

PIGMENTABLE MASTICS

Epoxy based glues such as EPOX PREMIUM and EPOX 2000

CHEMICAL PROPERTIES

ASPECT:	Paste
COLOUR:	See available colours
ODOUR:	Characteristic
SPECIFIC WEIGHT @ 20°C:	1,18 – 1,91 kg/dm ³ (based on type of colour)
SOLUBILITY IN WATER':	Insoluble
PH:	N.A.
STORED @ 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application. Add small amounts of EPO BEL to the epoxy glue to reach the desired tone or shade before adding the hardener. Note: Use one or mix multiple colours to obtain the desired match.

RECOMMENDATIONS

Add the hardener to the mix, after mixing the colouring paste to the glue.
Do not exceed the maximum amount of 6% in weight, doing so may affect the quality of the glue.
Keep away from heat, humidity and sunlight.

COLOUR CHART

						
308MCOLBI100 Bianco/White 100 ml	308MCOLBL100 Blu/Blue 100 ml	308MCOLGI100 Giallo/Yellow 100 ml	308MCOLMA100 Marrone/Brown 100 ml	308MCOLNE100 Nero/Black 100 ml	308MCOLRO100 Rosso/Red 100 ml	308MCOLVE100 Verde/Green 100 ml

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.

Disclaimer: the present information supersedes and replaces all previous versions. All data indicated in this document are the results of tests and experiments carried out in our laboratories and through reliable operators within the stone business and have to be considered reliable. However, because of the many external and surrounding factors which can influence the final results, the information here reported does not constitute an implicit or a formal guarantee. The end user will undertake the full responsibility in the usage of the product, making sure to test first the product and to experiment with the product as a preventive measure so to understand its full and final characteristics. Bellinzoni has to right to modify any information mentioned on this document, at any time and without notice. Bellinzoni is the sole owner of all trademarks and logos indicated in this document and to copy or modify in part or modify in part without permission can infringe property rights. Bellinzoni will not be held responsible for its incorrect use and will follow legal percussions as of current law.