

EUREKA GRANITE

PRODUCT DESCRIPTION

EUREKA is a waterless polishing gel, indicated for the polishing and gloss maintenance of various stone materials to obtain a quick and high surface gloss. EUREKA GRANITE is indicated for all granite and silica-based materials. Indicated for restoring gloss to surfaces in high traffic areas or for correcting gloss imperfections during the mechanical honing and grinding of surface .

APPLICATION SURFACES

Polished granite and silica- based materials

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Gel
COLOR:	Transparent cloudy
ODOR:	Odourless
SPECIFIC GRAVITY AT 20°C:	1,03 +/- 0,05 g/cm <sup>3</sup>
SOLUBILITY:	Soluble in all parts
PH:	5,7 +/- 0,05.
STORAGE AT 20°C:	24 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application. Ensure that surfaces to be treated are completely dry and clean, free of dirt, dust, grime and surface incrustations. Cover and protect all surrounding areas before proceeding with application. Remove any previous surface waxes or coatings (see our ULTRA STRIPPER) before proceeding with application  
**Floors:** Product is ready for use. Apply a small amount of product to the area (1m<sup>2</sup>) to be polished (30 gr or 1-2 teaspoons). Buff area using a white felt pad and mono brush machine (2.2HP – 150 rpm) in circular movements so to evenly distribute product to area. Continue to buff in wider circular movements until product is consumed completely. Apply second coat using the same procedure, until desired gloss is obtained. After treating areas, remove any excess dust from surface using clean cloth or dust mop. Rinse area using solution of water and LEM 3.

**Tables and countertops:** uProduct is ready for use. Apply a small amount of product to the area (1m<sup>2</sup>) to be polished (10-15gr or 1-2 teaspoons). Buff area using a variable speed rotary polisher and Eureka Pad at low speed in circular movements so to evenly distribute product to area. Continue to buff in wider circular movements until product is consumed completely. Apply second coat using the same procedure, until desired gloss is obtained. After treating areas, remove any excess dust from surface using clean cloth or dust mop. Rinse area using solution of water and B REFRESH TOP.

**Notes:** During application, product should be applied to materials with temperature between 10° and 30°C. Before application to floors with underfloor heating, turn off all heating and allow floor to cool completely before product application. Maintain product in its original container/packaging. Always test product first. in its original container/packaging. Always test product first.

RECOMMENDATIONS

Do not dilute with water or solvents. On extremely worn-down surfaces, we suggest 3 applications of product. For general gloss maintenance 1- 2 application are sufficient. Do not apply to wet surfaces. Apply product to small areas only. Before use, read completely product label, technical data sheet and safety data sheet.

INDICATED COVERAGE

With 1lt of product: 30/35 m<sup>2</sup>\*

(\*) depending on the number of coats, texture and porosity of the surface.

PACKAGING

CODICE	CONTENUTO	PZ CARTONE
081NGELGRA01	1lt	6
081NGELGRA05	5 lt	4
081NGELGRA25	25 lt	1

For further information: [www.bellinzoni.com](http://www.bellinzoni.com)

**ATTENTION:** Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.

Disclaimer: the present information supersedes and replaces all previous versions. All data indicated in this document are the results of tests and experiments carried out in our laboratories and through reliable operators within the stone business and have to be considered reliable. However, because of the many external and surrounding factors which can influence the final results, the information here reported does not constitute an implicit or a formal guarantee. The end user will undertake the full responsibility in the usage of the product, making sure to test first the product and to experiment with the product as a preventive measure so to understand its full and final characteristics. Bellinzoni has to right to modify any information mentioned on this document, at any time and without notice. Bellinzoni is the sole owner of all trademarks and logos indicated in this document and to copy or modify in part without permission can infringe property rights. Bellinzoni will not be held responsible for its incorrect use and will follow legal percussions as of current law.